


Aluminium column SAL-3/D60

114 mm at the base plate



TECHNICAL DATA

Anodising	10 colours
Luminaire mounting	directly on the column, luminaires with mounting $\varnothing 60$ mm with weight and surface parameters not exceeding the data from the strength table included in the technical data sheet
Extension arm type	according to resistance calculations
Packing	sleeve material
Performance under vehicle impact (passive safety)	50-NE-B-S-SE-MD-0, 70-NE-B-S-SE-MD-0, 100-NE-B-S-SE-MD-0
Diameter at the base plate	114 mm
Finish	brushed anodised aluminium - anode coating thickness is 20 μ m as standard (coating thickness of 25 μ m is also possible), option of elastomer protection in column's colour up to a height of 350 mm (other height on customer's request) - the thickness of the protective coating ranges from 0.8 mm to 1.2 mm
Ingress protection	IP54 for wire chamber
Diameter of the column ending	$\varnothing 60$ mm



STRENGTH TABLE

SAL-3/D60			Acceptable windage of single luminaire [m ²] for Cx=1			
code 42122			Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
code of extension arm	type of extension arm	permissible weight of a single luminaire [kg]	zone I, terrain category II	zone I & III, terrain category II up to 450m a.s.l	zone II, terrain category II	zone III, terrain category II up to 755m a.s.l.
-	-	20	0,92	0,77	0,64	0,56
471040	WA-4	10	0,57	0,46	0,35	0,29
471051	WA-5/1	10	0,29	0,23	0,17	0,14
471141	WA-14/1	10	0,37	0,29	0,22	0,18
471041	WA-41 f142	10	0,58	0,46	0,36	0,30
47204105	WR-4/1/0,5/5	-		ISKRA LED		
472041059	WR-4/1/0,5/5 ZP	-		ISKRA LED		
472831	WR-8B/1/0,35/0	-		ISKRA LED		
472841	WR-8B/1/0,35/5	-		ISKRA LED		
472851	WR-8B/1/0,35/10	-		ISKRA LED		

ANODISING COLOURS

